

CLAIMS

a step of receiving a packet containing a message requesting establishment of a connection with the server apparatus and an identification number for the connection sent from the user terminal according to a first communication protocol which is a protocol;

a step of receiving a packet containing a data transfer request message transmitted from the user terminal to the server apparatus according to the first communication protocol, and transmitting a packet containing this data transfer request message to the server apparatus according to the second communication protocol; and

wherein the first communication protocol is simpler than the second communication protocol.

2. A communication control method in a relay apparatus for relaying data communications between a server apparatus and a user terminal, comprising:

002120-62400960

a step of receiving a packet containing a message requesting establishment of a connection to the server apparatus, an identification number for the connection and a data transfer request message for the server apparatus
5 transmitted from the user terminal according to a first communication protocol;

a step of transmitting a packet containing an acknowledgment response message that the packet has been received to the user terminal according to the first
10 communication protocol, establishing a connection between the server apparatus and itself according to a second communication protocol, and transmitting a packet containing the data transfer request message to the server apparatus; and

15 a step of receiving data transmitted from the server apparatus according to the second communication protocol and transmitting a packet containing this data to the user terminal according to the first communication protocol;

wherein the first communication protocol is simpler
20 than the second communication protocol.

3. A communication control method according to claim 1 or 2, wherein the number of signals used in establishing the connection between the user terminal and the relay
25 apparatus according to the first communication protocol is less than the number of signals used in establishing the connection between the relay apparatus and the server apparatus according to the second communication protocol.

30 4. A communication control method according to claim 1 or 2, wherein a communication interval between the user terminal and the relay apparatus is composed of a radio-oriented interval, and a communication interval between the

5. A communication method for performing data communications between a server apparatus and a user terminal, wherein communication control procedure in an upper layer containing a transport layer in the data communications comprises:

a second step of transmitting a second packet containing an acknowledgment response message that this first packet has been received from the server apparatus to the user terminal; and

6. A communication method for performing data communications between a user terminal and a relay apparatus for relaying data communications between the user terminal and a server apparatus, wherein communication control procedure in an upper layer containing a transport layer in the data communications comprises:

a second step of transmitting a second packet



10

15

20

25

30

9. A server apparatus for performing data communications

with a user terminal, comprising:

communication control means for performing communication control at an upper layer level containing a transport layer when performing the data communications;

5 the communication control means comprising:

means for receiving a first packet containing a message requesting establishment of a connection and an identification number for the connection transmitted from the user terminal;

10 means for transmitting a second packet containing an acknowledgment response message that this first packet has been received to the user terminal; and

means for transmitting a third packet containing actual data to the user terminal by designating the identification number after the connection has been established with the user terminal.

10. A relay apparatus for relaying data communications between a server apparatus and a user terminal, comprising:

20 communication control means for performing communication control at an upper layer level containing a transport layer when performing the data communications;

the communication control means comprising:

25 means for receiving a first packet containing a message requesting establishment of a connection and an identification number for the connection transmitted from the user terminal;

30 means for transmitting a second packet containing an acknowledgment response message that this first packet has been received to the user terminal; and

means for transmitting a third packet containing actual data supplied from the server apparatus to the relay apparatus according to a predetermined protocol to the user

00600429-071200

terminal by designating the identification number after the connection has been established between the user terminal and itself.

11. A relay apparatus for relaying data communications between a server apparatus and a user terminal, comprising:
- means for receiving a packet containing a message requesting establishment of a connection with the server apparatus and an identification number for the connection transmitted from the user terminal according to a first communication protocol;
 - means for transmitting a packet containing an acknowledgment response message that the packet has been received to the user terminal according to the first communication protocol, and establishing a connection between the server apparatus and itself according to a second communication protocol;
 - means for receiving a packet containing a data transfer request message transmitted from the user terminal to the server apparatus according to the first communication protocol, and transmitting a packet containing this data transfer request message to the server apparatus according to the second communication protocol; and
 - means for receiving data transmitted from the server apparatus according to the second communication protocol and transmitting a packet containing this data to the user terminal according to the first communication protocol;
- wherein the first communication protocol is simpler than the second communication protocol.

12. A relay apparatus for relaying data communications between a server apparatus and a user terminal, comprising:

means for receiving a packet containing a message requesting establishment of a connection to the server apparatus, an identification number for the connection and a data transfer request message for the server apparatus
5 transmitted from the user terminal according to a first communication protocol;

means for transmitting a packet containing an acknowledgment response message that the packet has been received to the user terminal according to the first
10 communication protocol, establishing a connection between the server apparatus and itself according to a second communication protocol, and transmitting a packet containing the data transfer request message to the server apparatus; and

15 means for receiving data transmitted from the server apparatus according to the second communication protocol and transmitting a packet containing this data to the user terminal according to the first communication protocol;

wherein the first communication protocol is simpler
20 than the second communication protocol.

13. A relay apparatus according to claim 11 or 12, wherein the number of signals used in establishing the connection between the user terminal and the relay
25 apparatus according to the first communication protocol is less than the number of signals used in establishing the connection between the relay apparatus and the server apparatus according to the second communication protocol.

30 14. A relay apparatus according to any one of claims 10-12, wherein a communication interval between the user terminal and the relay apparatus is composed of a radio-oriented interval, and a communication interval between the

002120 62400360

5

10

means for transmitting a first packet containing a

15

20

25

30

means for transmitting a first packet containing a

message requesting establishment of a connection with the

relay apparatus and an identification number for the connection;

means for receiving a second packet containing an acknowledgment response message that the first packet has
5 been received transmitted from the relay apparatus; and

means for receiving a third packet containing actual data supplied from the server apparatus to the relay apparatus according to a predetermined protocol and transmitted from the relay apparatus by designating the
10 identification number after the connection has been established between the relay apparatus and itself.

18. A terminal device for performing data communications with a server apparatus via a relay apparatus for managing
15 a connection with the terminal device, comprising:

means for transmitting a packet containing a message requesting establishment of a connection with the server apparatus and an identification number for the connection according to a first communication protocol;

20 means for receiving a packet containing an acknowledgment response message that the packet has been received transmitted from the relay apparatus according to the first communication protocol;

means for transmitting a packet containing a data transfer request message to the server apparatus according
25 to the first communication protocol; and

means for receiving according to the first communication protocol a packet containing actual data supplied from the server apparatus to the relay apparatus
30 according to a second communication protocol in response to the data transfer request message;

wherein the first communication protocol is simpler than the second communication protocol.

09600429.071200

5 means for transmitting a packet containing a message requesting establishment of a connection with the server apparatus, an identification number for the connection and a data transfer request message for the server apparatus according to a first communication protocol;

10 means for receiving a packet containing an acknowledgment response message that this packet has been received transmitted from the relay apparatus according to the first communication protocol; and

means for receiving according to the first
15 communication protocol a packet containing actual data
supplied from the server apparatus to the relay apparatus
according to a second communication protocol in response to
the data transfer request message;

wherein the first communication protocol is simpler
20 than the second communication protocol.

20. A terminal device according to claim 18 or 19,
wherein the number of signals used in establishing the
connection between the user terminal and the relay
25 apparatus according to the first communication protocol is
less than the number of signals used in establishing the
connection between the relay apparatus and the server
apparatus according to the second communication protocol.

21. A terminal device according to any one of claims 17-19, wherein a communication interval between the user terminal and the relay apparatus is composed of a radio-oriented interval, and a communication interval between the

relay apparatus and the server apparatus is composed of a wire-oriented interval.

002120:071200